



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

## SERIES SPECIFICATIONS

AC Switch 15A 120V, Receptacle 15A 125V Combination Device  
 Combination devices allow for multiple controls in a single gang box to maximize space & efficiency  
 Terminal screws backed out and ready for installation  
 All devices have grounding terminals  
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention  
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention



## CONSTRUCTION

Color Ivory	Grade Residential	Device Type 1 Switch/1 Receptacle
Strap Material Galvanized Steel	Wires 2-Pole/3-Wire-Receptacle	NEMA Configuration 5-15R Receptacle
Operation Temperature From -40°C (without impact) to 75°C Maximum continuous	Environmental Rating Flammability UL94, V2 Rating	

## ELECTRICAL SPECIFICATIONS

Amperage 15 Ampere	Voltage 120V AC-Switch/125V AC-Receptacle	Poles Single Pole-Switch
Termination 1 Push-In #14 AWG Cu Solid wire only	Termination 2 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire	Grounding Capable Grounding
Wires 2-Pole/3-Wire-Receptacle		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

**CERTIFICATIONS/WARRANTY**

Listing  
UL Listed Listed

Warranty  
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

**ORDERING INFORMATION**

Part Number: C1R15-IV

Box Qty : 10

Weight (Lbs) : 0.175

Carton Qty. : 100

IMS Code : 0280-3947

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

