



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

AC Switch 15A 120V, Receptacle 15A 125V Combination Device
 Combination devices allow for multiple controls in a single gang box to maximize space & efficiency
 Terminal screws backed out and ready for installation
 All devices have grounding terminals
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention



CONSTRUCTION

Color Light Almond	Grade Residential	Device Type 1 Switch/1 Receptacle
Strap Material Galvanized Steel	Wires 2-Pole/3-Wire-Receptacle	NEMA Configuration 5-15R Receptacle
Operation Temperature From -40°C (without impact) to 75°C Maximum continuous	Environmental Rating Flammability UL94, V2 Rating	

ELECTRICAL SPECIFICATIONS

Amperage 15 Ampere	Voltage 120V AC-Switch/125V AC-Receptacle	Poles Single Pole-Switch
Termination 1 Push-In #14 AWG Cu Solid wire only	Termination 2 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire	Grounding Capable Grounding
Wires 2-Pole/3-Wire-Receptacle		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL Listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: C1R15-LA

Box Qty : 10

Weight (Lbs) : 0.175

Carton Qty. : 100

IMS Code : 0277-2642

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

