



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

AC Switch 15A 120V, Receptacle 15A 125V Combination Device
 Combination devices allow for multiple controls in a single gang box to maximize space & efficiency
 Terminal screws backed out and ready for installation
 All devices have grounding terminals
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention
 Receptacles have triple wipe line contacts and double wipe ground contacts to ensure long-term plug retention



CONSTRUCTION

Color
White

Grade
Residential

Device Type
1 Switch/1 Receptacle

Strap Material
Galvanized Steel

Wires
2-Pole/3-Wire-Receptacle

NEMA Configuration
5-15R Receptacle

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

Environmental Rating
Flammability UL94, V2 Rating

ELECTRICAL SPECIFICATIONS

Amperage
15 Ampere

Voltage
120V AC-Switch/125V AC-Receptacle

Poles
Single Pole-Switch

Termination 1
Push-In #14 AWG Cu Solid wire only

Termination 2
Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire

Grounding Capable
Grounding

Wires
2-Pole/3-Wire-Receptacle

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL Listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: C1R15-WH

Box Qty : 10

Weight (Lbs) : 0.175

Carton Qty. : 100

IMS Code : 0280-3944

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

