

MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

#### SERIES SPECIFICATIONS

15A 120/277V Four-Way Toggle Switch, Push-In/Side Wire Impact resistant, thermoplastic toggle & frame for increased durability Faster installation with push-in and side wiring options

Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)

Thick plated steel strap withstands abuse & corrosion





### CONSTRUCTION

Color Ivory

Strap Material Galvanized Steel Grade Residential Grade

Environmental Rating Flammability UL94, V2 Rating Device Type Toggle

Operation Temperature From -40°C (without impact) to 75°C Maximum continuous

## ELECTRICAL SPECIFICATIONS

Amperage 15 Ampere Voltage 120/277 V AC Poles 4-Way

Termination 1 Push-In #14 AWG Cu Solid wire only Termination 2 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire Grounding Capable

Grounding

### CERTIFICATIONS/WARRANTY

Listing UL Listed Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

# ORDERING INFORMATION

Part Number: FWT15-IV

Box Qty:10

Carton Qty.: 100

Weight (Lbs) : 0.1380

IMS Code : 0289-1121

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

