



MODEL :	TYPE
PROJECT :	
PREPARED BY :	DATE :

## SERIES SPECIFICATIONS

10/2 Landscape Cable, Low Voltage, Direct Burial, 500 Ft.  
UV Resistant for outdoor use  
Suitable for accent outdoor lighting, including landscape and security not exceeding 150V  
Rated for underground burial use  
Duplex flat construction for easy separation of conductors for installation



## CONSTRUCTION

Color Black	Data Rate 150V	Temperature Rating From -20°C to 60°C maximum
Conductor Material Copper	Shield Coverage N/A	Shield Material From -20°C to 60°C maximum
Jacket Flame Rate	Jacket Type PVC	

## ELECTRICAL SPECIFICATIONS

AWG 10	Conductors 2	Jacket Nom. Diameter N/A
Jacket Nom. Thickness 0.69 - 0.76	Wire Construction Stranded Flat	Conductor Construction 105 x 0.254
Resistance N/A		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

**CERTIFICATIONS/WARRANTY**

Listing  
UL listed Listed

Warranty  
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

**ORDERING INFORMATION**

Part Number: LV 10/2 - 500

Box Qty : 500 Ft.

Weight (Lbs) : 0.0931

Carton Qty. : 500 Ft.

IMS Code : 0256-4337

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

