



MODEL :	TYPE
PROJECT :	
PREPARED BY :	DATE :

SERIES SPECIFICATIONS

12/2 Landscape Cable, Low Voltage, Direct Burial, 100 Ft.
UV Resistant for outdoor use
Suitable for accent outdoor lighting, including landscape and security not exceeding 150V
Rated for underground burial use
Duplex flat construction for easy separation of conductors for installation



CONSTRUCTION

Color Black	Data Rate 150V	Temperature Rating From -20°C to 60°C maximum
Conductor Material Copper	Shield Coverage N/A	Shield Material From -20°C to 60°C maximum
Jacket Flame Rate	Jacket Type PVC	

ELECTRICAL SPECIFICATIONS

AWG 12	Conductors 2	Jacket Nom. Diameter N/A
Jacket Nom. Thickness 0.46 - 0.52	Wire Construction Stranded Flat	Conductor Construction 65 x 0.254
Resistance N/A		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: LV 12/2 - 100

Box Qty : 100 Ft.

Weight (Lbs) : 0.068

Carton Qty. : 600 Ft.

IMS Code : 0252-8796

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

