



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL: URD-NOTREDAME

SPECIFICATION & FEATURES

URD-NOTREDAME

This cable consists of several stranded, compressed 1350-H16/H26 aluminum wiring rated at 600V or less for direct burial use insulated with a cross-linked polyethylene. Conductor Material: AA 1350.

- ASTM B-230, B-231
- ASTM B-609, B-901
- UL Standard 854 requirement for USE-2
- ICEA S-105-692
- RoHS environmental conductive requirement



CERTIFICATIONS/WARRANTY

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

CONSTRUCTION

Voltage Rating 600V	Length 1000FT	Outside Diameter 0.362"(Phase),0.283"(Neutral)	Conductor Size 1/0 -1/0-1/0-2
Strands 19/7	Resistance 0.550/0.875Ω/km @20C	Temperature Rating 90°C	Number Of Conductors 4

Insulation Material

Cross Linked Polyethylene

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL:

ORDERING INFORMATION

Part Code	IMS Code
URD-WAKEFOREST	0599-0355

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

