



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL:

SPECIFICATION & FEATURES

Fire alarm cable is suitable for interconnection of electrical devices within a fire-protective signaling system. This wire is suitable for use in either dry or damp locations. It is made with solid copper conductors.



CONSTRUCTION

Wire Material
Annealed solid bare copper

Jacket Material
Red PVC

Insulation
PVC

Rating
UL (E464899) CL2 plenum
CL3P

Suggested Voltage Rating
300V

Operating Temperature
-20°C ~ 75°C

ORDERING INFORMATION

PART NUMBER	IMS CODE	AWG SIZE	NOM. DIA. INSULATION (MM)	NOM. DIA. JACKET (MM)
WC FPLP 14/2	0369-9021	14	2.3	5.33
WC FPLP 16/2	0369-9024	16	1.8	4.35
WC FPLP 16/4	0369-9027	16	1.8	5.13
WC FPLP 18/2	0369-9033	18	1.52	3.8
WC FPLP 18/4	0369-9036	18	1.52	4.45

NO. OF CONDUCTOR	COLOR
1	Black
2	Red
3	Brown
4	Blue



APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

11675 SW TOM MACKIE BLVD. | PORT ST. LUCIE, FL 34987 | P: 772.878.4944 | WWW.RPP-USA.COM