



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

15A 125V Tamper Resistant Single Receptacle, Side Wired
High-impact thermoplastic construction
Spring-loaded shutters lock out a single object, effectively blocking entry to the contacts
Clearly visible "Tamper Resistant" markings on face of device
Washer-type break off plaster ear for flush alignment



CONSTRUCTION

Color
Light Almond

Grade
Residential

Device Type
Single Receptacle

Strap Material
Steel

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

NEMA Configuration
5-15R

ELECTRICAL SPECIFICATIONS

Amperage
15 Ampere

Voltage
125 V AC

Poles
2

Termination 1
Side Wired, #12 AWG - #14
AWG Cu Solid or Stranded
wire

Termination 2

Grounding Capable
Grounding

Wires
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL Listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: SRTR15-LA

Box Qty : 10

Weight (Lbs) : 0.131

Carton Qty. : 100

IMS Code : 0288-1746

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

