



| | | |
|---------------|--------|--|
| MODEL : | TYPE | |
| PROJECT : | | |
| PREPARED BY : | DATE : | |

SERIES SPECIFICATIONS

15A 125V Duplex Receptacle, Side Wire, Commercial Grade
High-impact thermoplastic face and back is durable and long lasting, eliminating cracks and breaks
Captive mounting screws
Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)
Washer-type break off plaster ear for flush alignment



CONSTRUCTION

| | | |
|-----------------------------|--|--|
| Color Brown | Grade Commercial | Device Type Duplex Receptacle |
| Strap Material Steel | Environmental Rating Flammability UL94, V2 Rating | Operation Temperature From -40°C (without impact) to 75°C Maximum continuous |
| NEMA Configuration 5-15R | | |

ELECTRICAL SPECIFICATIONS

| | | |
|--|---------------------|--------------------------------|
| Amperage 15 Ampere | Voltage 125 V AC | Poles 2 |
| Termination 1 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire | Termination 2 | Grounding Capable Grounding |
| Wires 3 | | |

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





| | | |
|---------------|--------|------|
| MODEL : | | TYPE |
| PROJECT : | | |
| PREPARED BY : | DATE : | |

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: CR15-BR

Box Qty : 10

Weight (Lbs) : 0.169

Carton Qty. : 100

IMS Code : 0284-7177

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

