



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 125V Duplex Receptacle, Side Wire, Commercial Grade
 High-impact thermoplastic face and back is durable and long lasting, eliminating cracks and breaks
 Captive mounting screws
 Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)
 Washer-type break off plaster ear for flush alignment



CONSTRUCTION

Color Brown	Grade Commercial	Device Type Duplex Receptacle
Strap Material Steel	Environmental Rating Flammability UL94, V2 Rating	Operation Temperature From -40°C (without impact) to 75°C Maximum continuous
NEMA Configuration 5-20R		

ELECTRICAL SPECIFICATIONS

Amperage 20 Ampere	Voltage 250 V AC	Poles 2
Termination 1 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire	Termination 2	Grounding Capable Grounding
Wires 3		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: CR20-BR

Box Qty : 10

Weight (Lbs) : 0.163

Carton Qty. : 100

IMS Code : 0284-7180

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

