



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 120/277V Three-Way Toggle Switch, Push-In/Side Wire
 Impact resistant, thermoplastic toggle & frame for increased durability
 Faster installation with push-in and side wiring options
 Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)
 Thick plated steel strap withstands abuse & corrosion



CONSTRUCTION

Color
Brown

Grade
Commercial Grade

Device Type
Toggle

Strap Material
Galvanized Steel

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

ELECTRICAL SPECIFICATIONS

Amperage
20 Ampere

Voltage
120/277 V AC

Poles
3-Way

Termination 1
Push-In #14 AWG Cu Solid wire
only

Termination 2
Side Wired, #12 AWG - #14
AWG Cu Solid or Stranded
wire

Grounding Capable
Grounding

CERTIFICATIONS/WARRANTY

Listing
UL Listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

ORDERING INFORMATION

Part Number: CSB320-BR

Box Qty : 10

Weight (Lbs) : 0.1310

Carton Qty. : 100

IMS Code : 0279-6921

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM