




MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

15A 125V Decorator Duplex Receptacle, Push-In/Side Wire, Resi Grade
 High-impact thermoplastic face and back is durable and long lasting, eliminating cracks and breaks
 Dual-grounding options include grounding terminal or self-grounding clip
 Triple combination screws for fast wiring installation (Slotted, Phillips, & Robertson)
 Washer-type break off plaster ear for flush alignment



CONSTRUCTION

Color
White

Grade
Residential

Device Type
Duplex Receptacle

Strap Material
Steel

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

NEMA Configuration
5-15R

ELECTRICAL SPECIFICATIONS

Amperage
15 Ampere

Voltage
125 V AC

Poles
2

Termination 1
Push-In #14 AWG Cu Solid wire only

Termination 2
Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire

Grounding Capable
Grounding

Wires
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: DRD15-WH

Box Qty : 10

Weight (Lbs) : 0.119

Carton Qty. : 100

IMS Code : 0289-0677

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

