



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 125V Duplex Receptacle, Back/Side Wired, Hospital Grade
High-impact thermoplastic cover and body
Two side barriers cover the wire terminals for insulation and isolation, eliminating the need for taping wires
Break-off tabs for easy two-circuit conversion
Hospital Grade markings easy identifiable on face of device



CONSTRUCTION

Color
Ivory

Grade
Hospital

Device Type
Duplex Receptacle

Strap Material
N/A

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

NEMA Configuration
5-20R

ELECTRICAL SPECIFICATIONS

Amperage
20 Ampere

Voltage
125 V AC

Poles
2

Termination 1
Back Wired #10 - #14 wire

Termination 2
Side Wired, #12 AWG - #14
AWG Cu Solid or Stranded
wire

Grounding Capable
Grounding

Wires
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: HGR20-IV

Box Qty : 10

Weight (Lbs) : 0.181

Carton Qty. : 100

IMS Code : 0288-1704

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

