

SERIES SPECIFICATIONS

CONTRACTORPROJECTDATEPREPARED BYMODEL: LV 12/2-100

12/2 LANDSCAPE CABLE, LOW VOLTAGE, DIRECT BURIAL 100FT.

- UV Resistant for outdoor use
- Suitable for accent outdoor lighting, including landscape and security not exceeding 150V
- Rated for underground burial use
- Duplex flat construction for easy sepeartion of conductors for installation





CONSTRUCTION

Conductor 12 AWG Copper

Number of Conductors 2

Jacket Thickness 0.46-0.52 Nom.

Conductor Construction 65 x 0.254

Stranding

Stranded Flat

Jacket Color

Black

Color Black

> Jacket Material PVC

ELECTRICAL SPECIFICATIONS

Temp. Rating -20°C ~ 60°C Operating Voltage 150V

CERTIFICATIONS/WARRANTY

Listing UL Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





CONTRACTORPROJECTDATEPREPARED BYMODEL : LV 12/2-100

IMS Code : 0252-8796

ORDERING INFORMATION

Part Number: LV 12/2-100

Box Qty: 100 Ft.

Carton Qty: 600 Ft.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

