



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 125V Tamper Resistant Duplex Receptacle, Back/Side Wire
High-impact thermoplastic construction
Spring-loaded shutters lock out a single object, effectively blocking entry to the contacts
Clearly visible "Tamper Resistant" markings on face of device
Washer-type break off plaster ear for flush alignment



CONSTRUCTION

Color White	Grade Commercial	Device Type Duplex Receptacle
Strap Material Steel	Environmental Rating Flammability UL94, V2 Rating	Operation Temperature From -40°C (without impact) to 75°C Maximum continuous
NEMA Configuration 5-20R		

ELECTRICAL SPECIFICATIONS

Amperage 20 Ampere	Voltage 125 V AC	Poles 2
Termination 1 Back Wired #10 - #14 wire	Termination 2 Side Wired, #12 AWG - #14 AWG Cu Solid or Stranded wire	Grounding Capable Grounding
Wires 3		

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL Listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: TRCR20-WH

Box Qty : 10

Weight (Lbs) : 0.188

Carton Qty. : 100

IMS Code : 0284-6691

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

