



MODEL :	TYPE	
PROJECT :		
PREPARED BY :	DATE :	

## SERIES SPECIFICATIONS

15A 125V Tamper Resistant Duplex Receptacle, Push-In/Side Wired  
High-impact thermoplastic construction  
Spring-loaded shutters lock out a single object, effectively blocking entry to the contacts  
Clearly visible "Tamper Resistant" markings on face of device  
Washer-type break off plaster ear for flush alignment



## CONSTRUCTION

Color  
Ivory

Grade  
Residential

Device Type  
Duplex Receptacle

Strap Material  
Steel

Environmental Rating  
Flammability UL94, V2 Rating

Operation Temperature  
From -40°C (without impact)  
to 75°C Maximum continuous

NEMA Configuration  
5-15R

## ELECTRICAL SPECIFICATIONS

Amperage  
15 Ampere

Voltage  
125 V AC

Poles  
2

Termination 1  
Push-In #14 AWG Cu Solid wire  
only

Termination 2  
Side Wired, #12 AWG - #14  
AWG Cu Solid or Stranded  
wire

Grounding Capable  
Grounding

Wires  
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

**CERTIFICATIONS/WARRANTY**

Listing  
UL Listed Listed

Warranty  
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

**ORDERING INFORMATION**

Part Number: TRDR15-IV

Box Qty : 10

Weight (Lbs) : 0.131

Carton Qty. : 100

IMS Code : 0273-6705

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

