



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

Low Voltage Ceiling Mount Occupancy Sensor, Passive Infrared Technology

- 360 field of view, 1,200 sq. ft.
- Adjustable time delay
- Multi-level, 360 Fresnel lens for superior occupancy detection
- Sensitivity Adjustment 50% or 100% (DIP switch 1)
- Simple and fast installation



CONSTRUCTION

Color White	Mounting Ceiling	Operation Temperature 32°F to 131°F (0°C to 55°C)
Sensor Technology Passive Infrared	Time Delay 5 Seconds to 30 Minutes (DIP switch)	Light Level 10FC - 150FC
Coverage 1 Up to 1,200 square feet @ mounting height of 8 feet	Coverage 2 N/A	

ELECTRICAL SPECIFICATIONS

Voltage 24VDC	Poles N/A	Hertz N/A
Horsepower N/A	Time Delay 5 Seconds to 30 Minutes (DIP switch)	Load Rating 1 Current Consumption: 9mA
Load Rating 2 Power Supply: VCPP24 Power Pack	Load Rating 3 N/A	

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
cULus Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: VCMPC50L

Box Qty : 1

Weight (Lbs) : 0.394

Carton Qty. : 40

IMS Code : 0288-1731

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

