

SERIES SPECIFICATIONS

Passive Infrared Wall Mount Occupancy Sensor w/ AUTO/ON/OFF setting, 15A 120V, Single Pole Turns Light On/Off Automatically Adjustable time delay off setting from 15 seconds to 30 minutes Adjustable sensitivity settings Manual On/Off setting allows use as a regular switch Built-in photocell increases energy savings Decorator Wallplate Included Decorator Wallplate Included



CONSTRUCTION

Color Ivory

Sensor Technology Passive Infrared

Coverage 1 150, 450 square feet Mounting Wall

MODEL :

PROJECT :

PREPARED BY:

Time Delay 15 Seconds to 30 Minutes

Coverage 2 180, 500 square feet Operation Temperature 32°F to 131°F (0°C to 55°C)

Light Level 30 Lux-Daylight

ELECTRICAL SPECIFICATIONS

Voltage 120 V AC

Horsepower 1/8 HP

Load Rating 2 Flourescent lamp: 500 VA Poles Single

Time Delay 15 Seconds to 30 Minutes

Load Rating 3 Motor Load: 1/8HP Hertz 60 Hz

Load Rating 1 Incandescent lamp: 500 Watt

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 772.408.5213 WWW.RPP-USA.COM



TYPE

DATE :



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing cULus Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: VCOSW15-IV

Box Qty: 10

Carton Qty.: 40

Weight (Lbs) : 0.344

IMS Code : 0277-7094

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

