



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

Passive Infrared Vacancy Sensor w/ manual override switch, 15A 120V,
 Single Pole, Auto Off
 Manual On-Automatic Off
 Automatic off after time delay expires with manual "off" option
 Adjustable sensitivity settings
 Complies with California Title 24
 Decorator Wallplate Included



CONSTRUCTION

Color Ivory	Mounting Wall	Operation Temperature 32°F to 131°F (0°C to 55°C)
Sensor Technology Passive Infrared	Time Delay 15 Seconds to 30 Minutes	Light Level 30 Lux-Daylight
Coverage 1 150, 450 square feet	Coverage 2 180, 500 square feet	

ELECTRICAL SPECIFICATIONS

Voltage 120 V AC	Poles Single	Hertz 60 Hz
Horsepower 1/8 HP	Time Delay 15 Seconds to 30 Minutes	Load Rating 1 Incandescent lamp: 500 Watt
Load Rating 2 Flourescent lamp: 500 VA	Load Rating 3 Motor Load: 1/8HP	

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
cULus Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: VCSSVW15-IV

Box Qty : 10

Weight (Lbs) : 0.331

Carton Qty. : 40

IMS Code : 0277-7103

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

